



IMEXUS 28

Overall length	8,50 m
Waterline	8,05 m
Overall width	2,55 m
Width waterline	1,90 m
Submersion	0,30/1,45 m
Hinged centerboard	55 kg
Fixed ballast (additional option)	165 kg
Outer engine	5 HP - 120 HP
Mast length	9,00 m
Sailing: Grot/Fok/Genua	16,0/12,2/15,5 m ²
Height cabin	1,85 m
Clean water tank	2 x 12 ltr
Waste water tank	2 x 12 ltr
Weight	1.480 kg
Vacancies	6

Hull

- made of polyester resin, hand laminated, blue water line
- guard rail
- hinged centerboard 55 kg
- double rudder made of laminate
- deck transom suitable to finning an outboard engine up to 120 HP
- ballast tank approximately 730 ltr

Deck and equipment

- made of polyester resin, hand laminated construction, water-line and strip both made of blue gel-coat
- non-slip surface on passageways
- sliding cover and divided endwise cover made of acrylic-glass
- six windows in aluminium frame, four big window may be opened
- reversible blocks of halyards
- anchor locker with cover
- two seat – lockers in cockpit
- bath-platform
- place for portable or fixed fuel tank accessible from bath-platform
- steering station with big steering wheel
- tip-over seats in cockpit
- two capstans with clamp
- two stoppers of halyards
- genoa rails with blocks
- two long handrails
- mast stanchion
- sub-bonds of shrouds
- four bollards

- bow hatch
- stern baskets
- bow basket
- nautical rail
- bath ladder
- manual bilge pump

Interior equipment

- bottom and ceiling inserts made of polyester resin
- cabin walls covered with upholstery
- toilet, table, cabinets made of wood and oak wood
- floor with non-slip surfaces
- mattresses complete with thickness of 10 cm and 8 cm
- bunks on bow, stern and on sides
- folded table with build in bar
- lockers under bunks
- descent ladder into the cabin
- caboose equipped with sink, tap with electric pump and waste water portable tank
- toilet equipped with washbasin, tap with electric pump, clean and waste water portable tank and space for toilet
- shelves located on both sides of the bow bunk and one shelf located on the port side in stern section
- cabinets with opened doors on both sides of the cabin
- shelves for cups and dishes and additional shelf
- fire-extinguisher

Electric system

- main switch
- switchboard with six automatic fuses
- five lamps for living- room and toilet lighting
- battery 70 Ah with cables and clamps, tester to the battery
- white anchor light
- fix position lights complete
- compass
- plug 230 V from outside, switch FI
- plug 230 V next to switchboard

Rigging

- aluminum mast 9 metres, boom and spreaders
- stainless steel mast – step
- boom with rollers for reef ropes and honing tools of lower leech
- shrouds and stays made of stainless steel rope of 4 mm
- halyards guided inside the mast
- sub-bonds of halyards for mast lifting device
- tackle of the achter-stay
- tackle of the boom kicking strap
- main-sail on the mast hoops with one reef
- easy-reef system - I reef
- tackle of sheets of the main-sail
- foresail with sheets
- windex

/All information and prices are non-obliging. We reserve the right for mistakes and errors in text/